

Commercialization Strategy – Fuel Cell Vehicles

**Outline** 

- Technology "Road Map"
- Key Technology Objectives
- Technology Advancement Proof Points
  - -Catalyst development
  - -Understanding membrane failure
  - -Continuous Processing for cost reduction
- Demonstration fleets and field trials
- Summary



# Required Elements for Commercialization

**BALLARD®** 

FCV Commercialization

**Economic Incentive** 

Performance

Reliability

Cost

Field Validation/Service

Freeze Start

Durability

**Power Density** 

Cost

**Technology Demonstration** 

Fuel Cell

Balance of Plant


Electric Drive


**Fundamental Understanding** 


making fuel ce


**BALLARD®** 

2













- Execute Technology "Road Map" to demonstrate a commerciallyviable fuel cell technology by 2010
- Enhance strategic relationships with key unit cell component suppliers
  - Supply based needs to be encouraged to keep spending R&D dollars and to break the price/volume paradigm
- Accelerate emerging technologies; e.g.
  - Hydrocarbon composite membranes

**Technology Imperatives** 

- -Catalyst-loading reduction with enhanced voltage efficiencies
- Metal plate technologies

- Effective water management is essential to achieve performance and durability targets
  - Develop materials and design solutions, coupled with operational strategies that drive improved system efficiencies
- Accelerate design selection through improved "tools" and related modeling & simulation expertise
  - accelerated tests to define durability issues
- Engineered electrocatalyst layers
  - Catalyst loading reduction with improved performance; mitigation of known failure mechanisms

## Key Technology Development Objectives

- Low-cost composite membranes
  - Increased ionic conductivity and x-y plane dimensional stability
  - Introduce hydrocarbon ionomers
- Low-cost, continuous GDL deployment
  - -Facilitate continuous manufacturing process development for volume and cost reduction



Achieved further improvements in three key fuel cell stack performance metrics – in a single stack design...

#### Freeze Start

Performed 50
 consecutive
 freeze starts from
 -25° C (90 sec)

#### Durability


 Demonstrated stack lifetime of more than 2,000 hours

#### Cost Reduction

Reduce cost by 10% over 2004 technology

...while increasing stack power density and operational flexibility by running the durability test at reduced inlet Relative Humidity





## Catalyst Technology Advancements

**BALLARD®** 

**Platinum** 

1994

2004

Already Lab Demonstrated

>2010

8-10 mg/cm<sup>2</sup>

1.0 mg/cm<sup>2</sup>

0.3-0.5 mg/cm<sup>2</sup>

< 0.3 mg/cm<sup>2</sup>

**Processes** 

screen printing

spraying

roll coating (knife, comma bar)

CVD nanoparticle dispersion

coating

**Catalyst Structure** 

No catalyst support

Carbon Support Carbon Support Corrosion-free Support

Pt Metal

hand

Pt and Pt alloys

Pt and Pt alloys


Non-PGM or low Pt content alloys

making fuel cells a commercial reality


**BALLARD®** 

- Understanding failures:
  - Accelerated tests development and mechanistic understanding

 Mitigation and design improvements



Membrane is thinning in discrete areas





Reduced physical strength – leads to rupture

## Membrane Technology Advancements

**BALLARD®** 

10





#### **Chemistries**

Perfluoroionomer Perfluoroionomer Partiallyfluorinated

**Hydrocarbon?** 

# Cost Reduction - GDE Continuous Processing

**BALLARD°** 

11





**Finished substrate** 

**Hydrophobic treatment** 



**GDL Catalyst Coatings (GDE)** 

making fuel cells

## Durability as a Function of Operating Conditions

BALLARD®

12

180 kW



#### Mark 902 Heavy Duty Transportation

Pressure: 3 bara

Duty cycle: Medium

Dynamic

Durability: ~3,000 hr

85 kW



Mark 902 Light Duty Transportation

Pressure: 3 bara

Duty cycle: Fast

Dynamic

Durability: ~1,000 hr

4 - 21 kW



### Mark9 SSL<sup>™</sup> Forklifts

Pressure: 2 bara

Duty cycle: Slow

Dynamic

Durability\*: ~10,000 hr

\* Based on limited product test data

#### One design ...

- same stack technology meets needs of many applications
- durability is dependent on operating conditions




## How can California Help?



- Regulation is critical to drive growth in demonstration fleets CARB ZEV mandate
- Early adopters of fuel cell products state owned/run organizations
- State subsidy for "green" vehicles, during ramp to commercial volumes
- Stimulate growth and investment incentives for key component developers/suppliers
- BENEFITS: reduced urban pollution, reduced GHGs, energy reliability and diversity, contribution to sustainable energy future...











24 cities

- 4.5 million plus passengers
- Real world data

Vehicles powered by Ballard fuel cells have logged more than 2.6 million kilometers

BALLARD®

5








Residential Cogeneration: Mark 1030

Automotive: Mark 902

Materials Handling & Backup Power: Mark9 SSL™



- Execute the Technology "Road Map" to deliver fuel cell stack technology by 2010 that meets commercial targets when produced in high volume
- Accelerate the introduction of emerging technologies

Summary

- FCV commercialization will require regulation and subsidy
- FCVs must offer an economic incentive to the end-user
- Continue to leverage data from "real-life" field demonstrations
- Health and life style benefits of fuel cell technology products will be of great benefit to Californians